



DESTINATION FARM RADIAL IMPLEMENT TIRES



Firestone

F A R M T I R E S

THE LEADER IN THE FIELD



DESTINATION FARM RADIAL IMPLEMENT TIRES WITH AD2™ TECHNOLOGY:

DESIGNED, ENGINEERED AND BUILT FOR TODAY'S AGRICULTURE.

Firestone Destination Farm radial implement tires with Advanced Deflection Design (AD2) technology are designed to deliver a new level of performance in the operation and transportation of heavy farm equipment.

Available in IF or VF designations, these tires are engineered to carry more load at lower inflation pressures than conventional bias- or radial-ply implement tires. They also feature a soil-friendly tread design and a wider section width for greater contact area.*



A wider section width may significantly reduce soil compaction.

Firestone Destination Farm radial implement tires with AD2 technology are specifically designed for the high-load demands of today's agricultural equipment – tires that run on lower pressure, on a wider track and distribute the weight over a larger surface area to help reduce soil compaction.



*Compared to standard equivalent-sized Firestone bias and radial tires.



SPECIFICALLY DESIGNED FOR HEAVY FARM EQUIPMENT.


Considering the increasing size and weight of today's field implements – especially when loaded with the additional weight of herbicides, fertilizer and/or seed – soil compaction can actually be a bigger problem than the compaction from the tractor that pulls this equipment.

Producers who understand the costs of compaction from tractor tires are learning that implement tires cause yield-robbing compaction problems, too.


Until now, the default tire for most heavy farm equipment has been to use those built for trucks or buses. Firestone Destination Farm radial implement tires are specifically designed for the needs and demands of agriculture.



-- TEKSCAN FOOTPRINT COMPARISONS --




STANDARD BIAS
11L-15FI Highway Special, LR F
3960 lbs. @ 90 psi




IF DESTINATION FARM
IF280/70R15 Destination Farm, 128D
3960 lbs. @ 52 psi

Both IF and VF Destination Farm tires can carry more load at a lower pressure than standard equivalent-sized bias and radial tires. Lower pressure gives these tires a larger footprint and helps reduce soil compaction.



STANDARD RADIAL
295/75R22.5 TBR
6175 lbs. @ 110 psi



VF DESTINATION FARM
VF295/75R22.5
6400 lbs. @ 52 psi



THE AD² ADVANTAGE: MORE LOAD, BIGGER FOOTPRINT, LESS COMPACTION.*

Firestone Destination Farm radial implement tires with AD² technology offer superior performance compared to our standard radial tires. AD² is a new class of farm tires that helps improve the productivity of today's implements.

- IF-designated tires offer up to 20% more load-carrying capacity, or the same load at a lower pressure*
- VF-designated tires offer up to 40% more load-carrying capacity, or the same load at a lower pressure*
- Reduced soil compaction
- Wider section width for more contact area

DESTINATION FARM

| Tire Size | Material Number | Load Index | Speed Symbol Rating | Design Rim Width (in.) | Overall Width (in.) | Overall Diameter (in.) |
|-----------------|-----------------|------------|---------------------|------------------------|---------------------|------------------------|
| TUBELESS | | | | | | |
| IF240/80R15 | 000-543 | 121 | D | 8.00 | 9.70 | 30.10 |
| IF265/85R15 | 000-544 | 121 | D | 8.00 | 10.80 | 32.50 |
| IF265/85R15 | 001-585 | 125 | D | 8.00 | 10.80 | 32.50 |
| IF280/70R15 | 000-410 | 128 | D | 8.00 | 10.60 | 30.50 |
| VF245/70R19.5 | 000-555 | 134 | D | 7.50 | 9.40 | 33.40 |
| VF245/70R19.5 | 001-581 | 142 | D | 7.50 | 9.40 | 33.40 |
| VF265/70R19.5 | 000-896 | 141 | D | 7.50 | 9.90 | 34.40 |
| VF285/70R19.5 | 000-895 | 145 | D | 8.25 | 10.60 | 35.40 |
| VF255/70R22.5 | 000-898 | 146 | D | 8.25 | 10.30 | 37.30 |
| VF295/75R22.5 | 000-554 | 145 | D | 8.25 | 10.60 | 40.10 |
| VF295/75R22.5 | 001-583 | 151 | D | 8.25 | 10.60 | 40.10 |
| VF385/65R22.5 | 000-582 | 158 | D | 11.75 | 15.10 | 42.70 |
| VF385/65R22.5 | 000-899 | 163 | D | 11.75 | 15.10 | 42.70 |
| VF445/65R22.5 | 000-583 | 169 | D | 13.00 | 17.30 | 45.80 |
| VF445/65R22.5 | 001-584 | 174 | D | 13.00 | 17.30 | 45.80 |

| Static Loaded Radius (in.) | Rolling Circum. (in.) | Bar Height 32nds | Bar Height (in.) | Flat Plate (sq. in.) | Max. Load & Inflation (lbs. @ psi) |
|----------------------------|-----------------------|------------------|------------------|----------------------|------------------------------------|
| TUBELESS | | | | | |
| 13.40 | 90 | 11 | 0.34 | 66 | 3200 @ 46 |
| 14.40 | 96 | 11 | 0.34 | 86 | 3200 @ 35 |
| 14.40 | 96 | 11 | 0.34 | 86 | 3640 @ 41 |
| 13.40 | 92 | 11 | 0.35 | 78 | 3960 @ 52 |
| 14.50 | 100 | 19 | 0.59 | 70 | 4680 @ 58 |
| 14.80 | 100 | 19 | 0.59 | 74 | 5840 @ 75 |
| 15.50 | 103 | 20 | 0.63 | 92 | 6600 @ 75 |
| 15.90 | 106 | 21 | 0.65 | 100 | 7400 @ 75 |
| 16.80 | 112 | 26 | 0.83 | 85 | 6600 @ 75 |
| 17.40 | 121 | 19 | 0.59 | 105 | 6400 @ 52 |
| 17.80 | 121 | 19 | 0.59 | 109 | 7600 @ 64 |
| 18.40 | 128 | 23 | 0.71 | 144 | 9350 @ 58 |
| 18.50 | 128 | 23 | 0.71 | 144 | 10700 @ 70 |
| 19.80 | 138 | 24 | 0.75 | 189 | 12800 @ 64 |
| 19.60 | 138 | 24 | 0.75 | 194 | 14800 @ 75 |

*Compared to standard equivalent-sized Firestone tires.



WE PUT MORE INTO OUR TIRES SO YOU GET MORE OUT OF THEM.

Firestone farm tires with AD2 technology deliver the performance you want with the service and warranty you need. Visit your Certified Firestone Farm Tire Dealer and see for yourself.

- **The Certified Firestone Farm Tire Dealer** – specially trained and equipped to handle your in-field service needs.
- **The Firestone Farm Tire Warranty** – one of the best warranties in the farm tire business.
- **Extensive testing for durability and performance** at the Firestone Farm Tire Test Center in Columbiana, Ohio – the only farm tire test facility of its kind in the world.





WARRANTY

DESTINATION FARM RADIAL IMPLEMENT TIRES

LIMITED WARRANTY
FOR FIRESTONE DESTINATION FARM
RADIAL IMPLEMENT AGRICULTURAL TIRES



TIRES COVERED

This Limited Warranty covers original-tread Firestone brand radial agricultural tires purchased or manufactured after January 1, 2009, (except tires made for or used in pulling contests) if they are used in normal agricultural service. It does not cover tires marked "NO ADJ" or "NA" (non-adjustable), or tires not containing the Firestone serial number. Tires branded DT (damaged tire) are not adjustable for appearance. Tires are adjustable for ride-related conditions only during the first six months of service and up to 1/32nd of an inch of treadwear.

WHAT IS WARRANTED

If, before wearing down to 2/32nds of an inch of tread or bar depth remaining, any tire covered by this Limited Warranty becomes unusable for any reason within the manufacturer's control, such tire will be replaced with an equivalent new Firestone tire on the basis set forth in the section titled "Limited Warranty Period and Pro Rata Percentages" on the following page. Some examples of causes or conditions normally beyond the manufacturer's control are:

1. Field or road hazards or stubble damage (e.g. cut, snag, puncture, stubble damage, impact break, tear or chunk in tread, bar or shoulder);
2. Apparent overload or improper inflation pressure or abuse;
3. Wheel misalignment, rim slip, tire/wheel assembly imbalance, mismatching of adjacent tires, or other vehicle conditions, defects or characteristics;

LIMITED WARRANTY

FOR FIRESTONE DESTINATION FARM RADIAL IMPLEMENT
AGRICULTURAL TIRES

4. Conditions caused by land-leveling or earthmoving operations;
5. Improper repair or improper insertion of sealant, balancing, or filler materials;
6. Intentional alteration of either the appearance or the physical characteristics of the tire;
7. Mounting damage or conditions caused by aging or improper storage; and
8. Failure to observe any of the "Owner-User's Obligations" items listed elsewhere in this publication.

This Limited Warranty is in addition to, and/or may be limited by, any other applicable written warranty you may have received concerning special tires or situations.

LIMITED WARRANTY PERIOD AND PRO RATA PERCENTAGES

During the first two years of service (proof-of-purchase must be attached to claim form), if the tire is worn less than 25%, the tire will be replaced without charge including normal mounting and service charges.

After the free replacement period, the replacement price will be prorated based on years of service from the original purchase date (proof-of-purchase must be attached to claim form, or if proof-of-purchase is not available or if tire was not purchased new, then based on years from date of manufacture, which is molded into the sidewall of the tire) as set forth on the following page.

LIMITED WARRANTY

FOR FIRESTONE DESTINATION FARM RADIAL IMPLEMENT
AGRICULTURAL TIRES

| Years of Service or Age During | If Worn Less Than | Pro Rata Collection |
|-----------------------------------|----------------------|------------------------|
| 3rd Year | 30% | 30% |
| 4th Year | 40% | 40% |
| 5th Year | 50% | 50% |
| 6th Year | 60% | 60% |
| 7th Year | 70% | 70% |
| 8th Year | 80% | 80% |
| 9th Year | 90% | 90% |

After the end of the 9th Year, coverage expires. 100%

To determine the replacement price, the appropriate pro rata percentage is multiplied by the Firestone owner-user's regular buying price. Appropriate taxes, mounting, or other service charges will be added to the replacement price.

CONDITIONS AND EXCLUSIONS

To the extent permitted by law, Bridgestone Americas Tire Operations, LLC disclaims all warranties express or implied other than the warranties stated in this Limited Warranty, including but not limited to the implied warranties of merchantability and fitness for a particular purpose.

TO THE EXTENT PERMITTED BY LAW, BRIDGESTONE AMERICAS TIRE OPERATIONS, LLC DISCLAIMS LIABILITY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL AND PUNITIVE DAMAGES, LOSS OF TIME OR PROFITS, LOSS OF VEHICLE USE, OR INCONVENIENCE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH LOSS OR DAMAGES.

LIMITED WARRANTY
FOR FIRESTONE DESTINATION FARM RADIAL IMPLEMENT
AGRICULTURAL TIRES

Some states do not allow the exclusion or limitation of incidental or consequential damages, so this limitation or exclusion may not apply to you.

Only the actual owner-user of the covered tires may make an adjustment claim under this Limited Warranty and Commercial Adjustment Policy and only for tires used in the 50 United States and the District of Columbia.

Nothing in this Limited Warranty is intended to be a representation that failures cannot occur.

OWNER-USER'S OBLIGATIONS

Proper tire care is necessary to obtain maximum hours of usage and wear.

The owner-user's obligations are to operate tires within tire load and speed limits (at cold air pressures specified by Bridgestone Americas Tire Operations, LLC for load and speed according to individual tire size, type, and load capacity) and to maintain proper alignment of wheels.

In case of an adjustment claim, the owner-user must present the tire to an authorized Firestone dealer or store, complete and sign the customer section of the adjustment claim form, attach to the claim form a copy of the proof-of-purchase showing the date the tire was purchased new or proof-of-purchase of the new agricultural equipment that the tire came on, and pay the appropriate replacement price, taxes and service charges for a new, current equivalent Firestone brand tire.

LIMITED WARRANTY
FOR FIRESTONE DESTINATION FARM RADIAL IMPLEMENT
AGRICULTURAL TIRES

The obligation of Bridgestone Americas Tire Operations, LLC under this Limited Warranty and Commercial Adjustment Policy may not be enlarged or altered by anyone.

Copyright © 2013 Bridgestone Americas Tire Operations, LLC

PERFORMANCE REMINDER

Overloading and incorrect air pressure are two of the greatest causes of premature tire removal. For the best performance possible, select the proper design, size and ply-rated tires for your equipment and operate the tires at the inflation pressure required to carry the working load. Detailed load and inflation tables are included in the Firestone Farm Tire Data Book and at FirestoneAg.com.

PROPER TIRE SIZES

Tire sizes and ratings are dictated by vehicle geometry, weight and power. Before changing tire sizes, be sure to check with the equipment manufacturer or dealer. Tire measurements and load-carrying capacities for all Firestone agricultural tires are shown in the Firestone Farm Tire Data Book and at FirestoneAg.com. These measurements are especially important when matching front and rear sizes.

Have a technical question? Contact Firestone Field Engineering:
1-800-TIRE ENG (847-3364)

Need additional information?

FirestoneAg.com

Notes:



FirestoneAg.com

D-668 (11/14)



MIX
Paper from
responsible sources
FSC® C021255