



DuraForce Asphalt Paver (DFAP)

The American-made Firestone DURAFORCE Asphalt Paver is specially designed for challenging conditions in asphalt paving and repaving operations. Precision tractive effort is critical when operating pavers on sticky, fresh asphalt surfaces that heat up to 300 degrees Fahrenheit. Repaving operations grind out old asphalt, leaving ragged edges that chew up tire sidewalls. The DURAFORCE Asphalt Paver delivers optimum performance for such demanding operations, with features that deliver traction, withstand the heat and protect your tires.

SPECIALIZED FEATURES

- Notched rib pattern provides tractive performance on unimproved surfaces, including grass, dirt and gravel.
- Outside diameter ideal for restrictive asphalt paver wheel wells.
- Shallow E-7 tread depth helps manage heat from hot paving for longer service.



E-7 Shallow Tread Depth —
Helps manage heat from hot paving for longer service.

High Sidewall Gauge —
Thick sidewalls help protect the casing from scrubbing and abrasions.

35 psi Inflation Pressure —
Promotes flotation.



Large Contact Area —
Minimizes impact on newly paved surfaces.

Notched Rib Pattern —
Provides tractive performance on unimproved surfaces, including grass, dirt and gravel.

CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	MATERIAL #	AVG. WT.	OTD (32ND)	OVERALL DIAMETER	OVERALL WIDTH
LARGE TUBELESS	18.00-25	16		E-7	001277	321	16	60.3	18.9
LARGE TUBELESS	21.00-25	16		E-7	003771	422	16	66.4	24.3

NOTES:

Sidewall and tread compounds specially designed to resist diesel fuel used to clean the equipment.
Off Road tire limited warranty information is available from your Bridgestone authorized dealer or representative.
All specifications are estimates based on production model.